


# MIA SERIES



## MIA-X8-W

---

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988  
Fuente del Jarro - Valencia - Spain - Tel. +34961340860  
Updated (DD/MM/YYYY): 11/06/2026

 **DAS AUDIO**

## KEY FEATURES

- 2-way passive 8" coaxial point source system
- Uniform 110° conical coverage
- Frequency range (-10 dB) from 58 Hz to 20 kHz
- Maximum SPL of 126 dB
- Nominal impedance of 8  $\Omega$
- Dedicated FIR processing with INTEGRAL-MA

## DESCRIPTION

MIA-X8-W is a 2-way passive coaxial point source system designed to deliver accurate and consistent sound performance in applications requiring a compact, discreet, and high-quality solution. It features an 8" coaxial transducer that ensures excellent phase coherence and a balanced response across the audible spectrum, with a frequency range of 58 Hz to 20 kHz and a maximum sound pressure level of 126 dB SPL.

The coaxial configuration provides uniform 110° conical coverage, ensuring even sound dispersion and outstanding intelligibility regardless of the system orientation. This allows MIA-X8-W to be integrated into projects that require a compact, discreet solution capable of maintaining consistent coverage.

The system is manufactured from high-quality birch plywood with a durable polyurea paint finish. Its multi-angle design allows for flexible mounting in a wide variety of installation configurations, while the white finish enables seamless aesthetic integration into visually sensitive environments.

The system is equipped with M5 fixing points on the rear panel, allowing the use of dedicated mounting accessories for wall and/or ceiling installation. These accessories enable precise adjustment of both horizontal and vertical aiming angles, ensuring optimal coverage in each project.

With a nominal impedance of 8  $\Omega$ , MIA-X8-W allows up to 4 systems to be connected per amplifier channel, optimizing amplifier channel usage. In addition, dedicated FIR processing is available when used with INTEGRAL-MA matrix amplifiers, ensuring consistent system frequency response and optimized overall performance.

MIA-X8-W is a compact, efficient, and versatile solution for professional installed sound applications.

# MIA-X8-W

---

## SPECIFICATIONS

### Performance

Frequency Range (-10 dB)	58 Hz – 20 kHz
Nominal Impedance	8 ohms
Conical Coverage	110°
RMS Power Handling	250 W
Peak Power Handling	1000 W
On-axis Sensitivity 1W/1 m	96 dB SPL
Maximum Peak SPL at 1 m	126 dB
Recommended Amplifier	INTEGRAL-MA3004 INTEGRAL-MA1502
Recommended Processor	INTEGRAL-MA3004 INTEGRAL-MA1502

### Connectors

Audio Input Connector	4-way Phoenix 3.8 mm
-----------------------	----------------------

### Enclosure

Enclosure Construction	Birch Plywood
Enclosure Geometry	Trapezoidal
Rigging	M5 Thread Inserts
Finish	ISO-flex Paint
Color	Black
Dimensions ( H x W x D )	420 x 250 x 420 mm 16,6 x 9,9 x 16,6 in
Net Weight	10,8 kg ( 23,8 lb )

# MIA-X8-W


## Shipping

---

Carton Dimensions ( H x W x D )	505 x 320 x 350 mm 20,0 x 12,6 x 13,8 in
Shipping Weight	12,0 kg ( 26,5 lb )

---

## DIMENSIONS



# MIA-X8-W

---

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988  
Fuente del Jarro - Valencia - Spain - Tel. +34961340860  
Updated (DD/MM/YYYY): 11/06/2026

 **DAS AUDIO**

**ORDERING  
INFORMATION**

<b>Model</b>	<b>Description</b>	<b>P/N</b>
<b>System</b>		
MIA-X8-W		15006600

# MIA-X8-W

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988  
Fuente del Jarro - Valencia - Spain - Tel. +34961340860  
Updated (DD/MM/YYYY): 11/06/2026

