


**artec 300 series**



## **ARTEC-315.96-W**

---

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988  
Fuente del Jarro - Valencia - Spain - Tel. +34961340860  
Updated (DD/MM/YYYY): 14/04/2026

 **DAS AUDIO**

## KEY FEATURES

- 1 x 15MI low frequency loudspeaker, 2.5" VCD
- 1 x M-34 compression driver
- Rotatable 90° x 60° horn
- Vertical or horizontal positioning
- Optional AXU-AR315-W U-Bracket
- M10 rigging points

## DESCRIPTION

The ARTEC-315.96-W is a compact 2-way full-range loudspeaker system comprised of one 15" low frequency transducer and one M-34 compression driver with titanium diaphragm. The rotatable waveguide provides 90° x 60° coverage and allows the systems to be installed in either the vertical or horizontal position maintaining the needed dispersion characteristics.

The Artec-300 cabinets are constructed from Baltic Birch plywood and finished with a durable ISO-flex paint. The trapezoidal enclosure design helps eliminate standing wave coloration.

The cabinet is fitted with M10 threaded suspension points. Four VESA75/VESA100 standard threaded mounting points on the rear of the cabinet provide a secure fixing point for DAS mounting brackets.

# ARTEC-315.96-W

---

## SPECIFICATIONS

### Performance

Frequency Range (-10 dB)	60 Hz – 18 kHz
Horizontal Coverage (-6 dB)	90°
Vertical Coverage	60°
Nominal Impedance	8 ohms
RMS Power Handling	350 W
Peak Power Handling	1400 W
On-axis Sensitivity 1W/1 m	90 dB SPL
Maximum Peak SPL at 1 m	127 dB

Recommended Amplifier	INTEGRAL-A402
	INTEGRAL-A404
	INTEGRAL-A1002
	INTEGRAL-A1004
	INTEGRAL-A1602
	INTEGRAL-A1604
	INTEGRAL-MA1004
	INTEGRAL-MA1604
Recommended Processor	INTEGRAL-M88
	INTEGRAL-MA1604
	INTEGRAL-MA1004

### Connectors

Audio Input Connector	Covered Barrier Strip Terminals
Audio Output Connector	Covered Barrier Strip Terminals

# ARTEC-315.96-W

## Enclosure

Enclosure Construction	Birch Plywood
Enclosure Geometry	Trapezoidal
Rigging	M10 Rigging Points
Finish	ISO-flex Paint
Color	White
Dimensions ( H x W x D )	715 x 445 x 380 mm 28,2 x 17,5 x 15,0 in
Net Weight	22,5 kg ( 49,6 lb )

## Components


LF Driver	15MI
HF Driver	M-34
Horn/Waveguide	BC-916

## Shipping

Carton Dimensions ( H x W x D )	810 x 440 x 510 mm 31,9 x 17,3 x 20,1 in
Shipping Weight	24,5 kg ( 54,0 lb )

## DIMENSIONS

# ARTEC-315.96-W



# ARTEC-315.96-W

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988  
Fuente del Jarro - Valencia - Spain - Tel. +34961340860  
Updated (DD/MM/YYYY): 14/04/2026



## ORDERING INFORMATION

Model	Description	P/N
<b>System</b>		
ARTEC-315.96-W		10423858
<b>Replacement Parts</b>		
15MI	Cone Transducer	10214290
BC-916	Horn	30006590
F-AR315	Filter	30006593
GM-15MI	Recone Kit	20208270
GM-M34	Diaphragm	20205060
LAMP-F-21	Lamp	30000535
M-34	Compression Driver	10207080
<b>Accessories</b>		
AX-SPG1	Installation & Stacking Acc.	10105050
AXC-AT	Installation & Stacking Acc.	10104310
AXR-AR5-W	Installation & Stacking Acc.	10104880
AXU-AR315-W	Installation & Stacking Acc.	10105120
ANL-2	Rigging Accessories	10101020

# ARTEC-315.96-W

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988  
Fuente del Jarro - Valencia - Spain - Tel. +34961340860  
Updated (DD/MM/YYYY): 14/04/2026

