



## DESCRIPTION

The UX-221A make use of two 21" loudspeakers with impressive specifications. The 21UXN loudspeakers are equipped with 6" voice coils, a remarkable 60 mm peak to peak excursion, and powerful neodymium magnet assemblies. Efficient ventilation of the voice coil gap provides for a high thermal rating, and reduced power compression.

The UX-221A amplifier offers 2 x 3400 W and incorporates the latest in Class D power amplification. A high efficiency, low consumption universal power supply with Power Factor-Correction (PFC) allows for fail safe use worldwide. State of the art electronic design such as the fixed frequency switch mode output stage provides for the highest grade of audio accuracy. A comprehensive set of "smart" protections include thermal, over current, short circuit and overload on the output, clip limiter and high frequency protection keeping the amp and acoustic components safe.

The enclosure is constructed using 21 mm Birch plywood and makes use of extensive bracing to eliminate resonances. The woodwork is finished with the robust DAS ISO-flex protective coating for durability. A dolly platform with locking casters denominated the PL 221S is offered to stack and move the systems. Protection during transport is provided by the optional covers available from DAS.

## KEY FEATURES

- Powered ultra low frequency subwoofer system
- 2 x 3400 W Class D amplifier
- DASnet™ remote monitoring and control capable
- Twin 21" Neodymium loudspeakers with 6" voice coils
- Solid 21 mm Birch plywood construction
- Impressive 60 mm peak-to-peak excursion

## APPLICATIONS

- House of worship
- Theatres, auditoria and performing arts centers
- Live music clubs
- Corporate A/V
- Live sound touring/Rental services

## SPECIFICATIONS

### Performance

|                          |                |
|--------------------------|----------------|
| Frequency Range (-10 dB) | 28 Hz - 125 Hz |
| Maximum Peak SPL at 1 m  | 145 dB         |

### Electronics and Connectors

|                                      |                 |
|--------------------------------------|-----------------|
| Nominal Amplifier Power (continuous) | 2 x 3400 W      |
| Nominal Amplifier Power (peak)       | 2 x 6800 W      |
| Input Type                           | Balanced        |
| Input Impedance                      | 20 kohms        |
| Input Sensitivity                    | 4.9 V (+16 dBu) |
| Audio Signal Input Connector         | 1 x Female XLR  |
| Audio Signal Loop Thru Connector     | 1 x Male XLR    |
| Audio/Data Input Connector           | etherCON        |
| Control                              | DASnet™         |
| Audio + Data Loop Thru Connector     | etherCON        |
| AC Input Connector                   | powerCON TRUE1  |
| Operating Range                      | 90-250 VAC      |
| Current Draw 115 V                   | 18.4 A          |
| Current Draw 230 V                   | 9.2 A           |

### Enclosure

|                        |                    |
|------------------------|--------------------|
| Enclosure Construction | Birch Plywood      |
| Enclosure Geometry     | Rectangular        |
| Rigging                | M10 Rigging Points |



|                          |   |
|--------------------------|---|
| Finish                   | ISO-flex Paint                                  |
| Color                    | Black   |
| Dimensions ( H x W x D ) | 615 x 1.195 x 1.100 mm<br>24,2 x 47,0 x 43,3 in |
| Net Weight               | 150,0 kg ( 330,7 lb )                           |

### Components

|           |       |
|-----------|-------|
| LF Driver | 21UXN |
|-----------|-------|

### Shipping

|                                 |   |
|---------------------------------|---|
| Carton Dimensions ( H x W x D ) | 800 x 1.260 x 1.200 mm<br>31,5 x 49,6 x 47,2 in |
| Shipping Weight                 | 182,0 kg ( 401,2 lb )                           |

## ORDERING INFORMATION

### Performance

| Model | Description | P/N |
|-------|-------------|-----|
|-------|-------------|-----|

### System

|         |                   |          |
|---------|-------------------|----------|
| UX-221A | Powered Subwoofer | 10424860 |
|---------|-------------------|----------|

### Replacement Parts

|                 |              |          |
|-----------------|--------------|----------|
| 21UXN           | Transducer   | 20208810 |
| DIGIMOD-3000    | Amplifier    | 30008115 |
| GM-21UXN        | Recone Kit   | 20208480 |
| KIT-DSP-UX-221A | Dsp          | 20406561 |
| MP-UX-221A      | Power Module | 30006396 |

### Accessories

|              |                        |          |
|--------------|------------------------|----------|
| ANL-2        | Rigging Accessories    | 10101020 |
| EC-09        | Electronic Accessories | 20502110 |
| EC-2         | Electronic Accessories | 20502120 |
| EC-20        | Electronic Accessories | 20502130 |
| EC-30        | Electronic Accessories | 20502140 |
| ECP-20       | Electronic Accessories | 20502080 |
| ECP-3        | Electronic Accessories | 20502060 |
| ECP-30       | Electronic Accessories | 20502070 |
| ECPK-1       | Electronic Accessories | 20502090 |
| ECPK-20      | Electronic Accessories | 20502180 |
| ECPK-5       | Electronic Accessories | 20502100 |
| FUN-2-UX221  | Transport Accessories  | 10103690 |
| PL-221S      | Transport Accessories  | 10113210 |
| PLINK1-09    | Electronic Accessories | 20502150 |
| PWCONLINK-09 | Electronic Accessories | 20502210 |

## DIMENSIONS

