



DESCRIPTION

The EVENT-M210A is a three-way stage monitor in a double 10" "dual-band" configuration providing a wide frequency range. The DAS loudspeaker units have been teamed up with a single M-60 compression driver and purpose-designed injected aluminum high frequency waveguide.

The EVENT-M210A wedge is powered by a three channel Class D amplifier which provides 360 W_{peak} per channel. The amp's rear panel includes quality Neutrik® XLR and powerCON connectors, status LEDs to facilitate setup.

KEY FEATURES

- Light-weight Class D amplifier topology
- High-end DSP chipsets
- Special monitor Easy-DSP™ Interface
- Quality Neutrik® connectors
- Top grade Birch cabinet construction
- Durable ISO-flex finish
- Proprietary injected aluminum HF waveguide
- DAS M-60 compression driver

APPLICATIONS

- House of worship
- Theatres, auditoria and performing arts centers
- Live music clubs
- Corporate A/V
- Live sound touring/Rental services

SPECIFICATIONS

Performance

Frequency Range (-10 dB)	70 Hz - 20 kHz
Horizontal Coverage (-6 dB)	60°
Vertical Coverage	20°Up/30°Down
Maximum Peak SPL at 1 m	132 dB

Electronics and Connectors

Nominal Amplifier Power LF (continuous)	180 W
Nominal Amplifier Power LF (peak)	360 W
Nominal Amplifier Power MF (continuous)	180 W
Nominal Amplifier Power MF (peak)	360 W
Nominal Amplifier Power HF (continuous)	180 W
Nominal Amplifier Power HF (peak)	360 W
Input Type	Balanced
Input Impedance	20 kohms
Input Sensitivity	6.2 V (+18 dBu)
Audio Signal Input Connector	1 x Female XLR
Audio Signal Loop Thru Connector	1 x Male XLR
AC Input Connector	powerCon NAC3FCA
AC Output Connector	powerCON NAC3FCB
Operating Range	180-250 VAC
Current Draw 230 V	1.5 A



Enclosure

Enclosure Construction	Birch Plywood
Enclosure Geometry	Trapezoidal
Rigging	Captive Rigging System
Finish	ISO-flex Paint
Color	Black
Dimensions (H x W x D)	340 x 650 x 460 mm 13,4 x 25,6 x 18,1 in
Net Weight	23,5 kg (51,8 lb)

Components

LF Driver	10MI4
MF Driver	10MI4
HF Driver	M-75
Horn/Waveguide	BC-632

Shipping

Carton Dimensions (H x W x D)	740 x 370 x 490 mm 29,1 x 14,6 x 19,3 in
Shipping Weight	26,0 kg (57,3 lb)

ORDERING INFORMATION

Performance

Model	Description	P/N
-------	-------------	-----

System

EVENT-M210A-230	3-way powered Stage Monitor	10429210
-----------------	-----------------------------	----------

Replacement Parts

10MI4	Cone Transducer	20208770
BC-632	Horn	30006138
DSP-EVENT-M210A	Dsp	20406403
GM-10MI4	Recone Kit	20208420
GM-M75N	Diaphragm	20205080
M-75	Compression Driver	10208100
MP-EVENT-M210A- 230	Power Module	30006151
SMPS400A180	Power Supply	30008204

Accessories

PWCONLINK-09	Electronic Accessories	20502210
SC-1	Electronic Accessories	20501020
SC-10	Electronic Accessories	20501050

DIMENSIONS

