



## CL-8



### DESCRIPTION

The CL-8 is a 2-way passive full-range ceiling loudspeaker incorporating an 8" cone low frequency transducer and a ferrofluid cooled 1" soft dome high frequency unit with integral diffraction-ring. The system's low frequency driver is mounted on a plastic support with mounting tabs for fixing to ceiling surfaces. The front of the system is covered with a perforated metal grille.

### KEY FEATURES

- 8" ceiling mount loudspeaker
- 50 Hz – 20 kHz bandwidth
- 60 W<sub>rms</sub> power handling
- Polypropylene cone for durability

### APPLICATIONS

- Professional Installation Systems
- Houses of Worship
- Auditoriums/Theaters
- Hotel Ballrooms and Meeting Rooms

### SPECIFICATIONS

#### Performance

Frequency Range (-10 dB)	50 Hz – 20 kHz
Horizontal Coverage (-6 dB)	90°
Nominal Impedance	8 ohms
RMS Power Handling	60 W
Peak Power Handling	240 W
On-axis Sensitivity 1W/1 m	90 dB SPL
Recommended Amplifier	IA-402 IA-404

#### Connectors

Audio Input Connector	Spring Terminals
Audio Output Connector	Spring Terminals

#### Enclosure

Enclosure Geometry	Round
Color	White
Net Weight	1,9 kg ( 4,1 lb )

#### Shipping

Carton Dimensions ( H x W x D )	310 x 300 x 450 mm 12,2 x 11,8 x 17,7 in
Shipping Weight	2,1 kg ( 4,6 lb )



## ORDERING INFORMATION

---

### Performance

Model	Description	P/N
-------	-------------	-----

---

### System

CL-8	2-way Passive Co-axial	10213040
------	------------------------	----------

---

## DIMENSIONS

---

