



## CL-5-T



### DESCRIPTION

The CL-5T full-range ceiling loudspeaker incorporates a 5.25" double cone transducer with a 1" voice coil and 70V or 100 V line transformer. The system's low frequency driver is mounted to a plastic housing that includes the mounting tabs for fixing to ceiling surfaces. The front of the system is protected by a perforated metal grille.

### KEY FEATURES

- 5" ceiling mount loudspeaker
- 70 Hz – 15 kHz bandwidth
- Multi-tap 70V/100V Transformer
- Easy mounting system with built-in tabs

### APPLICATIONS

- Professional Installation Systems
- Houses of Worship
- Auditoriums/Theaters
- Hotel Ballrooms and Meeting Rooms

### SPECIFICATIONS

#### Performance

Frequency Range (-10 dB)	70 Hz – 15 kHz
Horizontal Coverage (-6 dB)	100°
Nominal Impedance	8 ohms
Transformer Taps 70 V	Tap1, 1.5 W. Tap2, 3 W. Tap3 6 W.
Transformer Taps 100 V	Tap1, 3 W. Tap2, 6 W. Tap3 X.
On-axis Sensitivity 1W/1 m	89 dB SPL
Recommended Amplifier	IA-402 IA-404

#### Connectors

Audio Input Connector	Spring Terminals
Audio Output Connector	Spring Terminals

#### Enclosure

Enclosure Geometry	Round
Color	White
Cut Out Diameter	169 mm (6,7 in)
Depth	70 mm (2,8 in)
Net Weight	0,9 kg ( 2,0 lb )

#### Shipping

Carton Dimensions ( H x W x D )	250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in
Shipping Weight	1,0 kg ( 2,2 lb )



## ORDERING INFORMATION

---

### Performance

Model	Description	P/N
-------	-------------	-----

---

### System

CL-5-T	2-way Passive Co-axial	10213020
--------	------------------------	----------

---

## DIMENSIONS

---

