



EVENT-26A

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988 Fuente del Jarro - Valencia - Spain - Tel. +34961340860 Updated (DD/MM/YYYY): 13/05/2025



KEY FEATURES

- · Ultra-compact, lightweight powered line array
- · High-efficiency Class D amplifier with SMPS
- · Dual voltage mains for use anywhere in the world
- · Easy system configuration thanks to DAScontrol™
- · High-end 24-bit DSP with LCD screen
- · FIR processing for constant phase response
- · FSS[™] Fast Set Splay rigging for quick deployment

DESCRIPTION

The EVENT-26A is a symmetrical, ultra-compact, two-way powered line array system. Designed by DAS engineers to deliver stunning performance and exceptional ease-of-use, the stylish polypropylene cabinet design offers a highly portable and road-worthy system. A comprehensive range of accessories makes the EVENT-26A ideal for small to mid-size rental and installation applications.

The EVENT-26A combines two 6.5" transducers and a single M-60 compression driver in a rugged yet lightweight polymer cabinet. The symmetric "V" shaped configuration of the cone transducers provides consistent 100° of horizontal coverage down to 300 Hz. The M-60 compression driver is coupled to an advanced waveguide design that provides control of the vertical dispersion as well as precise coupling between units when used in vertical arrays.

Powered by a two-channel Class D amplifier providing 800 Wpeak power, the amp's rear panel includes quality Neutrik® XLR and powerCON connectors. The DAScontrol™ interface makes the preset selection for the number of units in the array both fast and simple. An onboard DSP featuring a 24-bit high-end processor handles X-over, EQ, delay, and limiter functions. The powerful FIR filtering technology incorporated in the EVENT-26A offers constant phase response which translates to transparent sound and exceptional clarity, improving the listening experience.

Streamlined deployment of EVENT-26A arrays is possible thanks to the innovative FSS^{TM} (Fast Set Splay) rigging system developed to permit angle selection while stacked on dollies. The stainless-steel rigging hardware allows flown arrays of up to 16 units in 1° steps from 0° to 10°.

Low-frequency reinforcement for the EVENT-26A is provided by its flyable companion subwoofer the EVENT-115A.



SPECIFICATIONS

Performance

Frequency Range (-10 dB)	76 Hz - 19 kHz
Horizontal Coverage (-6 dB)	100°
Vertical Coverage	Color Doron dont
vertical coverage	Splay Dependent
Maximum Peak SPL at 1 m	131 dB

Electronics and Connectors

Nominal Amplifier Power (continuous)	400 W
Nominal Amplifier Power (peak)	800 W
Input Type	Balanced
Input Impeadance	20 kohms
Input Sensitivity	6.2 V (+18 dBu)
Audio Signal Input Connector	1 x Female XLR
Audio Signal Loop Thru Connector	1 x Male XLR
AC Output Connector	powerCON NAC3MPB
Current Draw 230 V / 115 V	0.8 A/1.6 A


Enclosure

Enclosure Construction	Polypropylene	
Enclosure Geometry	Trapezoidal	
Rigging	Captive Rigging System	
Color	Black	
Dimensions (H x W x D)	225 x 480 x 500 mm 8,9 x 18,9 x 19,1 in	



Net Weight	16,5 kg (36,4 lb)
Components	
LF Driver	6МІ
HF Driver	M-60
Shipping	
Carton Dimensions (H x W x D)	565 x 565 x 290 mm 22,2 x 22,2 x 11,4 in
Shipping Weight	20,0 kg (44,0 lb)

DIMENSIONS



ORDERING INFORMATION

Description	P/N
	10435010
Cone Transducer	20208985



DSP-EV26	Dsp	20406439
GM-M60N	Diaphragm	20205090
M-60	Compression Driver	20208790
MP-EV26A	Power Module	20405100
OR300+100UM	Amplifier	20406670
PIN-6	Pin	30002878
Accessories		
AX-EV26	Rigging Accessories	10102365
AXC-ZT	Installation & Stacking Acc.	10104320
AXS-EV26	Installation & Stacking Acc.	10102366
FUN-4-EV26	Transport Accessories	10103785
FUN-6-EV26	Transport Accessories	10103784
JP-EV26	Rigging Accessories	10102979
PL-EV26S	Transport Accessories	10113280
PWCONLINK-09	Electronic Accessories	20502210
SC-05	Electronic Accessories	20501010
SC-1	Electronic Accessories	20501020
SC-10	Electronic Accessories	20501050
TRD-6	Installation & Stacking Acc.	10104470
TRD-7	Installation & Stacking Acc.	10104471

