## **DECO** series



# **DECO 6 TB**

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988 Fuente del Jarro - Valencia - Spain - Tel. +34961340860 Updated (DD/MM/YYYY): 18/04/2024



#### **KEY FEATURES**

- · 6" ceiling mount loudspeaker with backcan
- ·70 Hz 20 kHz bandwidth
- · Multi-tap 70V/100V transformer
- · Easy mounting system with built-in tabs
- · Frameless grille design with black option

#### **DESCRIPTION**

The DECO series is a family of ceiling loudspeakers with minimum visual impact thanks to an innovative mechanical design that incorporates grilles attached with powerful neodymium magnets that cover the entire system so that it can blend seamlessly into its environment. All models in the series include loudspeakers with polypropylene cones, making them highly reliable in humid conditions. The design of the rubber mounts provides a high degree of movement and reduces low-frequency distortion levels. All models in the series are white, but black grilles are available as an option when used in spaces with dark ceilings.

The DECO-6TB is a wide-range passive two-way ceiling-mounted acoustic system featuring a 6.25" low-frequency cone loudspeaker and a 1" ferrofluid-cooled soft dome tweeter with an integrated diffraction ring. A frameless grille design means the system extends just 3 mm from the ceiling, making it practically invisible. It is equipped with a 15W 100V in-line transformer with multi-pass selector accessible from the front and it is designed for both high and low impedance. It includes a high pressure injected thermoplastic back cover.



#### **SPECIFICATIONS**


#### Performance

Frequency Range (-10 dB)	60 Hz – 20 kHz	
Nominal Impedance	8 ohms	
Conical Coverage	95°	
Transformer Taps 70 V	Tap0, Low Z. Tap1, 2.5 W. Tap2, 5 W. Tap3 7.5 W.	
Transformer Taps 100 V	Tap0, Low Z. Tap1, 5 W. Tap2, 10 W. Tap3 15 W.	
On-axis Sensitivity 1W/1 m	90 dB SPL	
Maximum Peak SPL at 1 m	112 dB	
Recommended Amplifier	INTEGRAL-A402 INTEGRAL-A404 INTEGRAL-A1002 INTEGRAL-A1004 INTEGRAL-A1602 INTEGRAL-A1604 INTEGRAL-MA1004 INTEGRAL-MA1604	
Recommended Processor	INTEGRAL-M88 INTEGRAL-MA1604 INTEGRAL-MA1004	
Connectors		
Audio Input Connector	Spring Terminals	
Audio Output Connector	Spring Terminals	



Enclosure Geometry	Round	
Color	White	
Cut Out Diameter	250 mm (9,9 in)	
Depth	185 mm (7,3 in)	
Dimensions ( H x W x D )	275 x 275 x 185 mm	
Birrierisieris (TTX VV X B )	11,0 x 11,0 x 7,3 in	
Net Weight	1,9 kg ( 4,2 lb )	
Shipping		
Carton Dimoncions (H v W v D)	310 x 300 x 450 mm	
Carton Dimensions ( H x W x D )	12,2 x 11,8 x 17,7 in	
Shipping Weight	2,2 kg ( 4,9 lb )	

#### **DIMENSIONS**







### ORDERING INFORMATION

Model	Description	P/N
System		
DECO-6-TB		10213206
Accessories		
GR-DC8	Installation & Stacking Acc.	20220502

