

# DECO series



## DECO-65-T

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988  
Fuente del Jarro - Valencia - Spain - Tel. +34961340860  
Updated (DD/MM/YYYY): 15/05/2025



SOUND WITH SOUL

## KEY FEATURES

- 2-way 6.5" Coaxial High-Performance Ceiling System.
- Multi-tap transformer 8 ohm & 70V/100V.
- Quick Install: Auto-locking tabs for secure, hands-free mounting.
- Easy Access: Front selector for hassle-free power adjustments.
- PK-65T accessory for versatile pendant mounting, available in white or black
- Frameless grille design, available in black.

## DESCRIPTION

The DECO-65-T is an advanced ceiling speaker system designed for top-tier audio performance and seamless aesthetic integration. Featuring a sturdy steel enclosure and a durable polypropylene front, it provides 120° conical coverage. Engineered for adaptability, it is equipped with a 4-way Phoenix connector for easy in and out link connections. The DECO-65-T operates at 8-ohm nominal impedance or in a 100V line system, with tap settings of 15W, 30W, and 60W accessible at the front. With an RMS power handling of 60W and a peak power of 240W, and a maximum peak SPL of 118 dB, it delivers robust and clear sound.

Its compact design, with a cut-out diameter of 245 mm (9.6 in), allows straightforward installation in various ceiling environments. Measuring 280 x 280 x 220 mm and weighing 4.3 kg (9.5 lb), it strikes a balance between size, power, and aesthetic discretion. The PK-65T accessory transforms it into a pendant speaker for greater placement flexibility and sound direction, especially beneficial in open architecture spaces or areas where traditional ceiling mounting is not optimal. Available in black and white finishes, the DECO series seamlessly matches any interior design.

For optimal performance, pair the DECO-65-T with the INTEGRAL-A402 or INTEGRAL-1004 amplifiers. Using the Integral Matrix and processors, fully compatible with ALMA™, enhances the speakers' capabilities through custom presets and comprehensive monitoring and control, ensuring effortless system management and maximum audio quality.

The modeling data for DECO-40-T / DECO-40-LP / DECO-65-T / DECO-80-T / DECO-80-TS are valid for EASE Focus, EASE Evac, and EASE Address.

# DECO-65-T

---

## SPECIFICATIONS

### Performance

Frequency Range (-10 dB)	60 Hz – 20 kHz
Nominal Impedance	8 ohms
Conical Coverage	120°
Transformer Taps 70 V	8 $\Omega$ / 7.5 W / 15 W / 30 W
Transformer Taps 100 V	8 $\Omega$ / 15 W / 30 W / 60 W
RMS Power Handling	60 W
Peak Power Handling	240 W
On-axis Sensitivity 1W/1 m	92 dB SPL
Maximum Peak SPL at 1 m	118 dB
Recommended Amplifier	INTEGRAL-A402
	INTEGRAL-A404
	INTEGRAL-A1002
	INTEGRAL-A1004
	INTEGRAL-A1602
	INTEGRAL-A1604
	INTEGRAL-MA1004
	INTEGRAL-MA1604
Recommended Processor	INTEGRAL-M88
	INTEGRAL-MA1604
	INTEGRAL-MA1004
	INTEGRAL-M26X

### Connectors

Audio Input Connector	4-way Phoenix 3.8 mm
-----------------------	----------------------

# DECO-65-T


Enclosure

Enclosure Construction	Steel
Enclosure Geometry	Round
Cut Out Diameter	245 mm (9,6 in)
Dimensions ( H x W x D )	280 x 280 x 220 mm 11,0 x 11,0 x 8,6 in
Net Weight	4,3 kg ( 9,5 lb )

Components

MF Driver	6B
HF Driver	TWT-65

DIMENSIONS



ORDERING

Model	Description	P/N
-------	-------------	-----

DECO-65-T

## INFORMATION

### System

DECO-65-T

10213238

### Replacement Parts

6B

Cone Transducer

20208260

TWT-65

Diaphragm

20209020

### Accessories

KIT-IP-DECO

Installation & Stacking Acc.

15001880

PK-65T

Installation & Stacking Acc.

10213410

PK-65TW

Installation & Stacking Acc.

10213440

SP-PRE-DECO-65T

Installation & Stacking Acc.

10213301

# DECO-65-T

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988  
Fuente del Jarro - Valencia - Spain - Tel. +34961340860  
Updated (DD/MM/YYYY): 15/05/2025



SOUND WITH SOUL